

MICR Cheque Scanner

FB-30

Compact & High Performance



- ❑ Processing speed up to 110 DPM (with standard 6 inches document in greyscale)
- ❑ Auto hopper / single stacker capacity – max 100 sheets
- ❑ MICR reading for E13B and CMC7
- ❑ Single line rear IJP for endorsement, or multiple lines (up to 4 lines) rear IJP for endorsement & capable of graphics print for logo, stamp and signature, etc.
- ❑ High quality colour, greyscale and black and white 300 dpi images
- ❑ Single feed for plastic non-embossed card scanning (ID, license card)
- ❑ UV image scanning
- ❑ Ultrasonic double feed detection for special paper (option)
- ❑ PC interface – image data and controls via USB 2.0
- ❑ Operating system – Windows 7 / 8 / 10

We Design Flexible Technology.

High Quality & Low cost MICR Teller Scanner

Providing Excellent Features from



GLORY FSM Ltd.

Specifications

| Type (options) | Included features |
|-------------------------|---|
| FB-30 | Standard unit |
| FB-30U | With UV image scanning |
| FB-30UW | With UV image scanning and Rear IJP for Multiple lines & Graphic printing |
| Document feeder | Type: Auto hopper Capacity: 100 documents (with 0.116mm thickness) Double feed detection: IR sensor < Ultrasonic sensor (option) > |
| MICR reader | Font read: E13B, CMC7 Number of characters: 65 characters or less Recognition rate: Greater than 99% |
| Endorser | Print head type: Ink jet: HP C6602A for Single line for FB-30/FB-30U Ink jet: HP C8842A/51645A for multiple (up to 4 lines) for FB-30UW |
| Image scanner | Capture module: Contact image sensor Capture side: Front and rear Representation: 8 bit grey / 24 bit colour (Jpeg or BMP) B/W (Tiff with G4 compression) Resolution: 200, 240, 300 dpi UV image: 8 bit grey UV image with 200 dpi for FB-30U/FB-30UW Scanning area (H × W): 108 × 235mm |
| Pocket | Capacity: 100 documents (1 pocket stacker) |
| Single feeder | Single feed scan: Plastic ID card single feed (non embossing) or single document feed |
| Processing speed | 8 bit grey: 110 DPM 24 bit colour: 65 DPM 8 bit grey with UV: 110 DPM |
| Document specifications | Length: 85mm – 235mm Height: 70mm – 120mm Thickness: 0.096mm – 0.156mm |
| System requirements | Operating system: Windows 7 / 8 / 10 |
| PC interface | USB 2.0 |
| Dimensions (W × D × H) | 335 – 405 × 148 × 188mm |
| Weight | 2.6kg (AC adapter not included) |
| Power | 24V DC adapter (100 – 240V, 50/60Hz) |

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by Glory Global Solutions. They may vary depending on usage conditions and are not guaranteed.



SECURA SYSTEMS LIMITED

A Reliable Machineries & Equipment Solution Provider

Rahman Chamber (1st & 6th Floor), 12-13, Motijheel, C.A, Dhaka-1000, Bangladesh
Tel: +880-2-223354650, 223389664, 223390415, Fax: 880-2-223383269
E-mail: shameem@securabd.com, Web: Web:sslbd.org